

TEST REPORT

Test	Description	Results	Standard
Dimensions	Length	± 0,5mm	UNE-EN ISO 10545-2
Surface Flatness	Curvature	± 0,5%	UNE-EN ISO 10545-2
Water Absorption	% Water	<0,5% (Bla)	UNE-EN ISO 10545-3
Modulus of Rupture	-	>35 N/mm ²	UNE-EN ISO 10545-4
Abrasion Resistance	Light	Class4	UNE-EN ISO 10545-77
	Dark	Class2	
Linear Thermal Expansion	-	Complies	UNE-EN ISO 10545-8
Resistance to Thermal Shock	No Enamel Cracks	Complies	UNE-EN ISO 10545-9
Crazing Resistance	No Enamel Cracks	Complies	UNE-EN ISO 10545-11
Frost Resistance	-	Complies	UNE-EN ISO 10545-12
Chemical Resistance	Household Chemicals	No Effect	UNE-EN ISO 10545-13
	Acids (Low concentration)	No Effect	
Stain Resistance	Ease of Cleaning	5 (Max)	UNE-EN ISO 10545-14
Slip Resistance	Pendulum (Spainn)	Class 2	UNE 41901 EX
	TRL Rubber (55)	>36 PTV	BS 77976-2
	45 Rubber (96)	>36 PTV	BS EN 13036-4
	SBR Rubber	>0,42 DCOF	ANSI A137.1
	Footwear Ramp	R10	DIN 51130
	Barefoot Ramp	B	DIN 51097

Important Notes:

The results in this report apply to the samples only.