

<b>Name of Sample</b>	MVG1794, 1795, 1796	<b>Shade</b>	V5
<b>Spacer</b>	2mm	<b>Size</b>	110x110mm
<b>m<sup>2</sup>/box</b>	0.411	<b>Thickness</b>	8.5mm
<b>Surface</b>	Anti-slip Matt	<b>pcs/box</b>	34 pcs
<b>Body</b>	Dry Pressed Porcelain Tiles		

Characteristics	Specification	NORM
<b>Water Absorption</b>	Eb ≤ 0,5%	UNE-EN ISO 10545-3:2018
<b>Modulus of Rupture</b>	≥ 35 N/mm <sup>2</sup>   ≥ 1300 N	UNE-EN ISO 10545-4:2019
<b>Abrasive Resistance</b>	PEI 2: Graphite   PEI 3: Green   PEI 4: Sand	UNE-EN ISO 10545-7:1999
<b>Crazing Resistance</b>	Pass	UNE-EN ISO 10545-11:1997
<b>Frost Resistance</b>	Pass	UNE-EN ISO 10545-11:1997
<b>Household Products Resistance</b>	GA	UNE-EN ISO 10545-13:2017
<b>Chemical Resistance</b>	GHA	UNE-EN ISO 10545-13:2017
<b>Stain Resistance</b>	5	UNE-EN ISO 10545-14:2015
<b>Non-slip Value</b>	R11 / CLASS 3 / DCOF >0,60	UNE-EN ISO 16165:2022 ANSI A137.1:2012
<b>Tone Variation</b>	V5	-
<b>Indoor &amp; Outdoor Use</b>	Indoor, Outdoor, Pool	
<b>Body Type</b>	Porcelain	WWS   WFA

#### TILE FIXING:

To ensure the products adhere correctly to the surface, it is essential to use specific adhesive and grouting material. This must also be suitable for the environment they will have to withstand. Fitting with traditional mortars does not ensure good adhesion. Due to the nature of the material there may be dimensional variations between pieces. Therefore, all types of joints must be planned and carried out correctly: structural, perimeter, expansion and installation joints. Fitting tiles without joints is not advisable from any technical point of view as this may lead to various problems. For an optimal result we advise to use 2 mm (0.08") grout, except for the Pixel model, for which a 1.5 mm (0.06") grout is recommended.

#### MAINTENANCE AND CLEANING:

Once the materials have been fitted, it is advisable to remove any remaining adhesive and grouting material by using a commercial descaling product designed especially, diluted with water. The descaling product must not remain in contact with the surface to be cleaned for more than 5 minutes. As a general guideline, powder detergents should not be used, not wire wool or abrasive materials. Generally a sponge will be sufficient with warm water and liquid neutral soap. Then rinse with plenty of clean water.

#### WARNING:

This collection reproduces traditional hand made tiles, this is the reason why there are slight dimensional differences between pieces (variable lengths and widths), which are part of the intended aesthetic. It is advised to adjust each one of the pieces in the process of installation due to the dimensional differences, instead of using spacers. As a result, these differences give the character, craftsman feel and a high aesthetic value.