

Name of Sample	MVG1836	Shade	V5
Spacer	2mm	Size	55x220mm
m²/box	0.411	Thickness	8.5mm
Surface	Matt	pcs/box	34 pcs
Body	Dry Pressed Porcelain Tiles		

Characteristics	Specification	NORM
Water Absorption	≤ 0,5%	UNE-EN-ISO-10545-3
Modulus of Rupture	≥35N/mm ² ≥1300N	UNE-EN-ISO-10545-4
Abrasive Resistance	PEI3	UNE-EN-ISO-10545-7
Linear thermal expansion	< 9*10 ⁻⁶ °C ⁻¹	UNE-EN-ISO-10545-8
Thermal shock resistance	Pass	UNE-EN-ISO-10545-9
Frost resistance	Pass	UNE-EN-ISO-10545-12
Domestic and swimming pool Chemicals	GA	UNE-EN-ISO-10545-13
Acids and alkalis of low concentration	GLA	UNE-EN-ISO-10545-13
Acids and alkalis of high concentration	GHA	UNE-EN-ISO-10545-13
Resistance to stains	5	UNE-EN-ISO-10545-14
Slip Resistance	Clase I R9 DCOF >0,42	UNE-EN 16165:2022 Anexo C+ANA UNE-EN 16165:2022 Anexo B ANSI A137.1
Resistance to the fire	Pass	Decisión 96/603/CE modificada