

TEST REPORT

Name of Sample	MVG1579, MVG1580, MVG1581, MVG1582, MVG1583	Body	Porcelain White Body
Group	Bla GL Dry-pressed Glazed Ceramic Tiles	Size	115x231x8.2mm

SIZE SPECIFICATIONS		
Test	Required Standard EN14411	Standard
Orthogonality N N<7cm y Hexagono N>=15cm 7<N<15cm	s.n. ± 0,5% ± 0,75 mm	UNE EN ISO 10545-2
Thickness	± 0,5 mm	
Superficial Flatness (Central, lateral / Warp) N < 7cm N >= 15cm 7 < N < 15cm	s.n. ± 0,5% ± 0,75 mm	
Work Size N < 7cm N > 15cm 7 < N < 15cm	± 0,5 mm ± 0,6% ± 0,9 mm	
Surface Quality	>= 95%	

PHYSICAL SPECIFICATIONS		
Test	Result	Standard
Water Absorption	E <= 0.5%	UNE EN ISO 10545-3
Flexure Resistance	>35 N/MM2	UNE EN ISO 10545-4-9
Breaking Strength	>1300 N	UNE EN ISO 10545-4
Crazing Resistance	ACCOMPLISH	UNE EN ISO 10545-11
Frost Resistance	ACCOMPLISH	UNE EN ISO 10545-12
Abrasion Resistance		UNE EN ISO 10545-7
Mohs Hardness	5	UNE EN 67-101
Slip Resistance		UNE-EN 16165 Anexo C PENDULUM BS 7976-2 (WET) PENDULUM AS 4586:2013 (WET) PENDULUM UNE-EN 16165 Anexo B RAMP UNE-EN 16165 Anexo A RAMP ANSI A326.3 DCOF

CHEMICAL SPECIFICATIONS		
Test	Result	Standard
Resistance to stains	5	UNE EN ISO 10545-14
Resistance to cleaning products Resistance to low concentration of acids and alkalis	A	UNE EN ISO 10545-13